



(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
03.05.2000 Bulletin 2000/18

(51) Int. Cl.⁷: **H04M 3/523, H04M 3/51**

(21) Application number: **99308215.5**

(22) Date of filing: **18.10.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**

Designated Extension States:
AL LT LV MK RO SI

(30) Priority: **29.10.1998 US 182353**

(71) Applicant:
**LUCENT TECHNOLOGIES INC.
Murray Hill, New Jersey 07974-0636 (US)**

(72) Inventors:
• **Flockhart, Andrew D.**
Thornton, Colorado 80241 (US)
• **Foster, Robin H.**
Little Silver, New Jersey 07739 (US)
• **Mathews, Eugene p.**
Barrington, Illinois 60010 (US)

(74) Representative:
Johnston, Kenneth Graham et al
Lucent Technologies (UK) Ltd,
5 Mornington Road
Woodford Green Essex, IG8 OTU (GB)

(54) **Method and apparatus for giving dissatisfied call center customers special treatment**

(57) In a call center (100) of a business, if it is determined (314-318 or 320) during the handling of a call involving a party who is a customer of the business that the party is at risk of being lost as a customer to the business, an identifier of the party, such as ANI, is captured (300) and stored (322) along with an "at risk" indication. The determination may be made either automatically by detecting (314-318) that the party terminated the call while on hold, or manually (320) by the agent handling the call or a service observer whereupon the agent or observer pressed an "at risk" feature

button (112) on their terminal (105, 110). On a subsequent call to or from that party, the stored identifiers (380) are searched (306), and when it is determined (308) that the party is identified therein as being at risk, the call is given (310) special treatment (400-426)—a higher-than-normal level of service—and is identified (428) to the call's handler as involving an "at risk" customer, in an attempt to avoid loss of the party as a customer.




FIG. 1

Description

Technical Field

[0001] This invention relates to call centers, also commonly referred to as automatic call distribution systems and telemarketing systems.

Background of the Invention

[0002] Studies have shown that it is much more cost-effective for a company to retain an existing customer than it is to try to win a new customer. They have also shown that the most common reason for a customer to switch suppliers is because of poor service and not because of any complaint about the product being purchased. Providing good customer service and preserving the loyalty of existing customers is therefore one of the primary objectives of today's businesses. Consequently, the ability to identify "at risk" customers who have received poor service or are otherwise dissatisfied, and to take steps to correct the problem before the customer is lost, is of prime importance to a business.

[0003] Large businesses generally provide a significant amount of their customer service telephonically via call centers. Their approaches to maintaining customer satisfaction with customer service focus on agent training and service observing in an attempt to maintain high standards of service. But even if they meet their objectives, it is inevitable that there will be at least some instances of customer service that, for one reason or another, leave a customer dissatisfied. A solution for the problem of identifying and retaining such "at risk" customers is therefore needed.

Summary of the Invention

[0004] This invention is directed to solving the problems and meeting the needs of the prior art. Illustratively according to the invention, the solution is to capture identifiers (e.g., the calling number, or ANI) of calling or called parties who are deemed to be "at risk", and to provide special call treatment for these parties when they contact the company again (or when the company contacts them). The intent is to offer a higher-than-normal level of service to these parties in an attempt to avoid the loss of their business. (The term "call" is used broadly herein to encompass any communication.)

[0005] For an automated implementation, one of the clearest signs that a party has received poor service and is probably highly frustrated is that the party abandons after being answered by an agent. The most common cause is because the agent has placed the call on hold and failed to return to the call in an acceptable period of time. This is one event that can be programmed to identify an "at risk" customer.

[0006] For manual implementation, agents and service observers can be given new feature buttons or

other actuators which can be used while a call is active to identify and automatically log the ANI of any party whose business is deemed to be "at risk".

[0007] Generally according to the invention, a method of handling communications, e.g., at a call center, involves the following: While handling a first communication involving a party thereto, determining that the party is (actually or potentially) dissatisfied with the handling. In response, storing an indication of the party's dissatisfaction. Then, in response to a second communication involving that party, determining from the stored indication that this party was dissatisfied, and therefore providing special handling of the second communication to alleviate the party's dissatisfaction. The party is also preferably identified to a handler of the second communication as a dissatisfied party. Illustratively, the special handling involves at least one of (a) having a handler other than a handler of the first communication handle the second communication, (b) having the second communication handled by a specialist, (c) having the second communication handled by a supervisor of communication handlers, (d) avoiding handling the second communication by a non-human handler (e.g., an interactive voice response unit), (e) handling the second communication as a high-priority communication, and (f) handling the second communication immediately and out of turn with other communications that are waiting to be handled.

[0008] While characterized above as a method, the invention also encompasses an apparatus that performs the method, and a processor-readable medium containing software which, when executed in a processor, causes the processor to perform the method. The apparatus preferably includes an effector—any entity that effects the corresponding step, unlike a means—for each method step.

[0009] These and other features and advantages of the present invention will become clearer from the following description of an illustrative embodiment of the invention considered together with the drawing.

Brief Description of the Drawing

[0010]

FIG. 1 is a block diagram of a call center that includes an illustrative embodiment of the invention; FIG. 2 is a flow diagram of operations of an "at risk" customer function of an ACD switch of the call center of FIG. 1; and

FIG. 3 is a flow diagram of operations of a special treatment function of the ACD switch of the call center of FIG. 1.

Detailed Description

[0011] FIG. 1 shows a call center 100 that is interconnected with telephones 101-102 of callers who are

potential users of call center 100 by a telephone network 103. Call center 100 comprises an automatic call distribution (ACD) switch 104, a plurality of agent positions 107-108, and a supervisor and/or service observer position 109. Each agent position 107-108 comprises a call-handling terminal 105, such as a display telephone or a voice-enabled data terminal, and is staffed by a call-handling agent 106. Supervisor/observer position 109 comprises a supervisor's/observer's terminal 110 that has abilities beyond call handling, such as call monitoring of calls being handled by agents 106, etc., and is staffed by a supervisor/observer 111. ACD switch 104 conventionally includes trunk ports 200 for connecting ACD switch 104 to telephone network 103; line ports 201 for connecting ACD switch 104 to agent positions 107-108 and supervisor position 109; service circuits 203 that provide various services, such as tone generators, announcement generators, hold circuits, conference circuits, modems, interactive voice-response units, etc.; a switching fabric 202 that selectively interconnects ports 200, ports 201, and service circuits 203; a processor 204 that controls switching fabric 202 and other elements of ACD switch 104; and a memory 205 which holds control programs and data which processor 204 executes and uses to control then operation of ACD switch 104. Memory 205 includes queues 130-131 for calls that cannot be handled immediately, and an estimated waiting time (EWT) function 206 which computes the amount of time that a call is likely to spend in any one of the queues 130-131 before being taken out of the queue, e.g., before being connected to an agent position 107-108. ACD switch 104 is illustratively the Lucent Technologies Definity[®] ACD private branch exchange (PBX). As described so far, call center 100 is conventional.

[0012] According to the invention, memory 205 includes an "at risk" customer function 207 for execution by processor 204. Operations performed by function 207 are shown in the flowchart of FIG. 2. Execution of function 207 by processor 204 is invoked either in response to arrival at ACD switch 104 of a new call for which the calling number, account number, or some other caller identifier, has been obtained (e.g., via automated number identification (ANI), a voice response unit (VRU), or some other mechanism) by ACD switch 104, or in response the placing of a call by ACD switch 104 to a known number, at step 300. Processor 204 evaluates the obtained identifier to determine if it is valid, at step 302. For example, in the case of ANI of a newly-arrived call, processor 204 checks the "ii" digits that accompany the calling number to determine if the call is from a paystation, a hotel room, or a roaming cellular radiotelephone; if so, the identifier is deemed to be invalid (because it cannot be determined who the caller is from such a calling number). In the case of an account number or a personal identification number (PIN), processor 204 checks a database (not shown) of valid account numbers and PINs to determine if the

obtained identifier appears therein. If the case of an outbound call to a known number, the identifier (the called number) is valid a-priori.

[0013] If the identifier is determined to be invalid, the call will be processed conventionally, and so execution of function 207 ends with respect to this call, at step 324. If the obtained identifier is determined to be valid, processor 204 compares the obtained identifier against contents of an "at risk" database 380 which contains identifiers of customers who are deemed to be at risk, at step 306, to determine if the calling or called party to the call is designated therein as an "at risk" customer, at step 308. If so, the call is marked for special treatment, at step 310; if not, the call will be processed conventionally. Special treatment of an "at risk" customer's call may constitute any desired treatment. For example, the call may be given a high priority, so that it does not have to wait in a call queue 130-131 as long as other calls, or may even bypass queues 130-131 altogether and be assigned to an agent 106 immediately and out of turn with other calls that are waiting to be handled. Also, the call may be marked for handling by one of the call center's best-qualified agents 106, or even by supervisor 111. Also, an indication (e.g., a displayed message) is given to agent 106 or supervisor 111 to whom the call is assigned for handling, that this is a call involving an "at risk" customer so that the call handler can make an extra effort to satisfy this customer.

[0014] An example of special treatment that may be implemented by ACD switch 104 is flowcharted in FIG. 3. First, a determination is made, from customer records kept by call center 190, whether this calling or called party to the call is a top-tier (preferred) customer, at step 402. If so, a determination is made of whether an agent 106 who is a specialist is available to handle the call, at step 404. If so, the call is routed to the specialist for handling, at step 426, and the party is identified (e.g., via a message displayed on the handling agent's terminal) to the handler as an "at risk" customer, at step 428. Returning to step 404, if it is determined that a specialist is not available, EWT function 206 is used to determine whether the in-queue wait time will exceed a threshold (e.g., 10 seconds), at step 410. If not, the call remains in a queue 130-131 to eventually be routed to an available agent 106 for handling, at steps 426 et seq. If the in-queue wait time will exceed the threshold, the call is routed to supervisor 111 for handling, at step 412, and the party is identified to supervisor 111 as an "at risk" customer, at step 428.

[0015] Returning to step 402, if the party is not a top-tier customer, call records and/or database 380 are checked to determine if the party became an "at risk" customer today, at step 414. If so, the call is marked for personal service (e.g., no use of call prompting or interactive voice response, etc.), at step 416, for service observing by a supervisor/observer 111, at step 418, and for handling by an agent 106 other than the one who handled the party's previous call, at step 420. The

call then remains in queue to eventually be routed to an available agent 106 for handling, at steps 426 et seq. Returning to step 414, if the party did not become an "at risk" customer today, the call is marked as a high-priority call so that it will receive priority treatment over other calls, at step 422, and is eventually routed to an available agent 106 for handling, at steps 426 et seq. Following step 428, the special treatment ends, at step 430.

[0016] Returning to FIG. 2, following step 308 or 310, processor 204 continues to monitor the call until it ends, as determined at step 312, whereupon execution of function 207 ends for this call, at step 324. While the call is being monitored, if it is delivered to an agent 106 for handling, as determined at step 314, is subsequently put on hold, as determined at step 316, and is abandoned (i.e. the party hangs up) while it is on hold, at step 318, the customer is considered to be "at risk", and so processor 204 enters the obtained identifier of the party in "at risk" database 380, at step 322. Optionally, a callback call to the customer may be made at this time from ACD switch 104 so that the agent 106 who handled the call or the supervisor 111 may apologize to the party and complete the interrupted transaction with the party. Additionally, if the agent 106 who is handling the call or a supervisor/observer 111 decides for some reason during the handling of the call that this customer is "at risk" and manually actuates an "at risk" actuator on their terminal 105 or 110 (e.g., by pushing an "at risk" button 112 or typing a corresponding entry), at step 320, processor 204 enters the identifier of the party in "at risk" database 380, at step 322. An agent may perceive a customer to be "at risk" if, for example, the customer expresses anger, dissatisfaction, frustration, or a complaint about the company or its service or product. Following step 322, execution of function 207 ends for this call, at step 324.

[0017] Of course, various changes and modifications to the illustrative embodiment described above may be envisioned. For example, the system can mark a customer as being "at risk" if, while in queue, the customer abandons the call after an exceptionally long wait. Also, a customer may be manually marked in the database as being "at risk" if some form of communication expressing a complaint or other dissatisfaction was received from the customer. Such changes and modifications can be made within the scope of the invention and without diminishing its attendant advantages. It is therefore intended that such changes and modifications be covered by the following claims.

Claims

1. A method of handling communications CHARACTERISED BY the steps of

while handling a first communication involving a party to the first communication, determining (316-320) that the party is dissatisfied with the

handling;

in response, storing (322) an indication of the party's dissatisfaction;

in response to a second communication involving the party, determining (306-308) from the stored indication that this party was dissatisfied; and

in response, providing special handling (310, 400-430) of the second communication to alleviate the party's dissatisfaction.

2. The method of claim 1 wherein:

determining that the party is dissatisfied comprises one of

- (a) detecting (320) actuation of an actuator, whose actuation indicates the dissatisfaction, by one of a handler of the first communication and a service observer of handling of the first communication, and
- (b) detecting (316-318) termination of the first communication while the first communication is on hold.

3. The method of claim 1 wherein:

determining from the stored indication that this party was dissatisfied comprises one of (a) receiving (300) the second communication from the party and (b) placing (300) the second communication to the party; and in response, checking (306) stored indications for presence of the stored indication that this party was dissatisfied.

4. The method of claim 1 wherein:

providing special handling comprises at least one of (a) having (420) a handler other than a handler of the first communication handle the second communication, (b) having (404) the second communication handled by a specialist, (c) having (412) the second communication handled by a supervisor of communication handlers, (d) avoiding handling (416) the second communication by a non-human handler of communications, (e) handling (422) the second communication as a high-priority communication, and (f) handling (410) the second communication immediately and out of turn with other communications that are waiting to be handled.

5. The method of claim 1 wherein:

providing special handling comprises identifying (310, 418) the party as dissatisfied

to a handler of the second communication.

6. The method of claim 1 wherein:

determining that the party is dissatisfied com- 5
prises
while handling a first call involving a party who
is a customer of a business at a call center,
detecting one of (a) actuation (320) of an actu- 10
ator whose actuation indicates that the party is
at risk of being lost as a customer to the busi-
ness, by an agent who is handling the first call
or by a service observer who is observing the
handling of the first call, and (b) termination 15
(316-318) of the first call after it has been put
on hold by the agent and while it is on hold;
storing an indication of the party's dissatisfac-
tion comprises
capturing (300) an identifier of the party, and
in response to the detection, storing (322) the 20
identifier as an indication that the party is at risk
of being lost as a customer to the business;
determining from the stored indication that the
party was dissatisfied comprises
one of (c) receiving (300) a second call from 25
the party and (d) placing (300) a second call to
the party, and
in response, checking (306-308) stored indica-
tions for presence of the stored indication that
the party is at risk of being lost as a customer 30
to the business; and
providing special handling of the second com-
munication comprises
in response to presence of the stored indica-
tion, providing (310) special handling of the 35
second call comprising at least one of (e) hav-
ing (420) an agent other than the agent who
handled the first call handle the second call, (f)
having (404) the second call handled by a spe-
cialist, (g) having (412) the second call handled 40
by a supervisor of the agents, (h) avoiding han-
dling (416) the second call by a non-human
handler of calls, (i) handling (422) the second
call as a high-priority call, and (j) handling (410)
the second call immediately and out of turn 45
with other calls that are waiting to be handled,
and
identifying (428) the party to the handler of the
second call as being a party at risk of being lost
as a customer to the business. 50

7. An apparatus (104) CHARACTERISED IN THAT it
performs the method of claim 1 or 2 or 3 or 4 or 5 or
6.

55

8. The apparatus of claim 7 comprising an automated
call distribution system (104).




FIG. 1

FIG. 2





FIG. 3





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number

EP 99 30 8215

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 0 755 144 A (AT & T CORP) 22 January 1997 (1997-01-22) * abstract; figure 1 * * page 3, line 27-35 *	1-4,7,8	H04M3/523 H04M3/51
X	HARRIS FOSTER R: "IN THE FOREFRONT WITH INTEGRATED CALL CENTERS" AT & T TECHNOLOGY, US, AMERICAN TELEPHONE & TELEGRAPH CO. SHORT HILLS, NEW JERSEY, vol. 7, no. 4, 1 January 1992 (1992-01-01), pages 8-13, XP000371952 ISSN: 0889-8979 * page 9, right-hand column - page 10 *	1-8	
			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
			H04M
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 3 March 2000	Examiner Cremer, J
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03.92 (POMC01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 8215

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

03-03-2000

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0755144 A	22-01-1997	US 5684872 A	04-11-1997
		AU 703432 B	25-03-1999
		AU 6056096 A	30-01-1997
		CA 2174978 A	22-01-1997
		JP 9149137 A	06-06-1997
<hr/>			

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82